



Lufft OPUS20 - An essential data collector for all calibration laboratories measuring precise temperature, relative humidity and air pressure!

- **Parameters measured** Temperature, relative humidity and air pressure
- Measurement technology Temperature & air pressure / NTC, Humidity / Capacitive
- Product highlights LAN datalogger with built-in sensors and highest precision, evaluation software SmartGraph3 included
- Interfaces USB (Cable and SmartGraph3 monitoring software included)

The only LAN datalogger with built-in sensors and the highest precision! Firmware online updatable. The OPUS20 runs on batteries or powered via USB. Alternatively, you have the possibility to power the device via POE (Power over Ethernet).

General	
Dimensions	166 x 78 x 32 mm
Measuring interval	10/30 s, 1/10/12/15/30 min, 1/3/6/12/24 h
Construction	Plastic housing
Operating time with battery	>1Year

IMPORTANT: OPUS 20 THIP is discontinued

1-2

We reserve the right to make technical changes and improvements without The superior of the su



Technical Data

OPUS 20 THIP - discontinued

Data storage	16 MB, 3,200,000 measured values
LC-Display	Height 90 x 64 mm
Weight	Approx. 250 g
Included in delivery	PC - Windows Software SmartGraph 3
	For graphical and numerical representation
	of measured values / instruction manual / data cable / battery /
	DIN rail bracket
Interface	USB, LAN
Storage interval	1/10/12/15/30 min, 1/3/6/12/24 h
Power supply	4 x LR6 AA Mignon, USB
Operating temperature	-2050 °C
Operating rel. humidity	0100 % RH, < 20 g/m ³ (non - condensing)
Max. height	10,000 m above sea level

Temperature	
Principle	NTC
Measuring range	-20 50 °C
Unit	°C
Accuracy	±0.3 °C (040 °C), otherwise ± 0.5 °C
Resolution	0.1

Relative humidity	
Principle	Capacitive
Measuring range	0 100 % RH
Unit	% RH
Accuracy	±2 % RH
Resolution	0.1

Air pressure	
Measuring range	300 1300 hPa abs.
Unit	hPa abs.
Accuracy	7001100 hPa at 25 °C ±0.5 hPa
Resolution	0.1